

Dingo Cement Pty Ltd

Unit 8 27-35 Huntingdale Rd
Burwood 3125 Victoria Australia
Phone: +61 3 8080 1420



www.dingocement.com.au

Product Data Sheet

Flashcrete Mortar

Features & Benefits

Flashcrete is a mix of sand, cement, and premium grade additives for fast repairs. Suitable for around the home and building site, patching around electric & plumbing fittings, re-pointing on block, brick, and render walls.

Sets in 5 minutes.

Packaging

Flashcrete comes in a handy 8kg plastic bucket.

Curing

Flashcrete cures over 28 days.

Storage and Tools

Store in a dry place. Ensure unused material is covered.

Tools required - concrete trowel, bucket, wheelbarrow, straight edge shovel or rake.

Coverage

Toilet Pan

1 x 8kg bucket = 0.5m² at 10mm thick.

An 8kg bucket will provide sufficient mortar to bed one toilet pan.



Usage

1. Slowly add clean water into the Flashcrete bucket.
2. Place lid firmly back on bucket. Roll and shake bucket for one minute.
3. Mix thoroughly and place immediately.

Excess water will weaken the strength of this product.

NOTE: approx. 1.6 litres of water to an 8kg bucket of Flashcrete.

Handy Hints

- Do not use mechanical mixer for this product.
- If priming surfaces with water, use of an acrylic bonding agent assists adhesion.

Precautions for use

For detailed precautions, please download the SDS from www.dingocement.com.au or call 03 8080 1420.

Read the product label carefully before use.