

Dingo Cement Pty Ltd

Unit 8 27-35 Huntingdale Rd
Burwood 3125 Victoria Australia
Phone: +61 3 8080 1420



www.dingocement.com.au

Product Data Sheet

Fast Set Sand & Cement

Features & Benefits

Fast Set Sand & Cement is a mix of sand, cement, and premium grade additives. This product will harden in approximately 15 minutes.

Applications

- Repairs around the home and building site
- Patching around electrical and plumbing fittings
- Re-pointing on block, brick and rendered walls
- Where ever fast repairs are needed to masonry surfaces.

Packaging

Fast Set Sand & Cement is packaged in 20kg water resistant plastic bags.

Curing

Fast Set Sand & Cement hardens in approximately 15 minutes and cures fully over 28 days.

Mixing

Empty bag into a wheelbarrow or non-porous surface. Add drinkable water slowly and mix to a workable consistency.

Apply the mixed product with a trowel.

Approximately 2.8litres of water to a 20kg bag.

Small amounts can be mixed in a bucket, just add water, and add your dry mix Fast Set Sand & Cement.

Storage and Tools

Concrete trowel, timber float, wheelbarrow, straight edge shovel & garden rake. Clean tools after use. Store in dry place and cover unused materials.



Usage

1. Make sure the surface is free of dust.
2. Lightly mist the area with drinkable water.
3. Apply the Fast Set Sand & Cement mix as needed to complete the job. Mix and place within 5 minutes.
4. Allow the Fast Set Sand & Cement mix to slightly harden before finishing with wooden float, steel trowel or a clean damp sponge.

Excess water will weaken the strength of this product.

Coverage

One 20kg bag covers approximately 1.1m² with a 10mm thickness.

Tips

Use Oxide to colour the Fast Set Sand & Cement.

Only mix enough material that can be used within a reasonable time frame.

Precautions for use

For detailed precautions, please download the SDS from www.dingocement.com.au or call 03 8080 1420.

Read the product label carefully before use.