

Dingo Cement Pty Ltd

Unit 8 27-35 Huntingdale Rd
Burwood 3125 Victoria Australia
Phone: +61 3 8080 1420



www.dingocement.com.au

Product Data Sheet

Sand & Cement

Features & Benefits

Sand & Cement is a mix of washed sand and general purpose cement. Suitable for many purposes, it is a general purpose mortar product.

Applications

- Patching around electrical / plumbing fittings
- Re-pointing on block, brick & render walls
- Bedding for shower bases & toilet pans
- General brick laying

Packaging

Sand & Cement is packaged in 20kg water resistant plastic bags.

Curing


Sand & Cement cures over 28 days.

Mixing

Empty bag into a wheelbarrow or non-porous surface. Add drinkable water slowly and mix to a workable consistency. Approximately 2.8litres of water to a 20kg Sand & Cement bag.

Storage and Tools

Concrete trowel, timber float, wheelbarrow, straight edge shovel & garden rake. Clean tools after placing S&C. Store in dry place and cover unused materials.



Usage

1. Make sure the surface is free of dust.
2. Lightly mist the area with drinkable water.
3. Apply the Sand & Cement mix (S&C) as needed to complete the job.
4. Allow the S&C mix to dry before finishing with wooden float, steel trowel or a clean damp sponge.

Excess water will weaken the strength of this product.

Precautions for use

For detailed precautions, please download the SDS from www.dingocement.com.au or call 03 8080 1420. Read the product label carefully before use.

Coverage

One 20kg bag covers approximately 1.1m² with a 10mm thickness.

Tips

Use Oxide to colour the Sand & Cement. Only mix enough material that can be used within a reasonable time frame.