Dingo Cement Pty Ltd

Unit 8 27-35 Huntingdale Rd Burwood 3125 Victoria Australia

Phone: +61 3 8080 1420



Product Data Sheet

Dingo Mortar Mix

Features & Benefits

A dry mix combination of sand, cement and lime, provides excellent workability in a variety of uses. Dingo Mortar Mix conforms to AS3700 (M3 Mortar).



Applications

- Paving
- BBQ cementing blocks
- Rendering over brick, concrete and masonry surfaces.
- Garden beds
- Fixing toilet pans and associated pipes.

Coverage

Bricks

1 bag lays up to 26 clay bricks 52 clay bricks = 1m² (110mm thick)

Blocks

1 bay lays up to 15 standard blocks 12.5 standard blocks = 1m² (100mm thick) Excessive water will weaken the mortar. Mortar Mix contains lime, do not use near fish ponds.

Storage and Tools

Store in a dry place. Ensure unused material is covered.

Tools required - concrete trowel, bucket, wheelbarrow, straight edge shovel or rake.

Usage

- 1. Empty Mortar Mix into wheelbarrow or onto a clean, non-porous surface.
- Slowly add water, (maximum of 4 Litres) mixing until a stiff yet workable consistency is reached. The mix should just slip off the trowel when lightly flicked.
- Your mortar is now ready to trowel onto bricks or blocks.
- 4. Cure your finished mortar by keeping it moist & covered for a minimum of seven (7) days before use.

Handy Hints

- Clay bricks should be lightly soaked in water before laying.
- Concrete blocks should be laid dry.
- Retaining walls should not be backfilled for at least 2 weeks.

Packaging

Dingo Mortar mix is packaged in 20kg plastic bags.

Precautions for use

This product contains cement.

For detailed precautions, please download the SDS from www.dingocement.com.au or call 03 8080 1420.

Read the product label carefully before use.