Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

BITUMEN

Australia's favourite Bitumen repair for Professionals, Councils and DIYers. Specifically engineered to remain somewhat pliable following application. This assists in eliminating small voids and crevices through the compaction process.

Key Features

- ✓ Ready to use - just pour and compact
- ✓ Fast, Easy & Permanent
- ✓ Open to Traffic Immediately
- ✓ Waterproof bag

Popular Uses

- Potholes
- Driveways
- Footpaths
- Speed humps
- General Repairs

Directions for use

PLEASE READ CAREFULLY BEFORE OPENING BAG.

- Area where product is to be used must be dry
- Remove any weeds or other plant material (use of weed killer recommended)
- For footpaths use timber or other material to assist forming edges
- Base must be thoroughly compacted, crushed stone recommended
- Apply material evenly, do not exceed 30mm in one application, leave for a few minutes and then compact using a roller, plate compactor or hand tamper
- A 30mm layer should compact to around 25mm
- For thicknesses greater than 50mm Dingo Bitumen is not recommended
- A light covering of sand is recommended to allow usage straight away.
- If the bag is firm to touch, leave in a warm place for 30 minutes. Place at ambient temperature, then no reheating is required
- Product hardens slowly as the bonding agent dries out. This progresses over several weeks depending upon application and weather conditions. During this period scuffing should be avoided. Driveway sealers or coatings to the repaired area should be avoided until after 6 months

Yield

60kg of Dingo Bitumen will cover approximately 1m² at a depth of 23mm.

Safety

IF SWALLOWED

- Drink water, seek medical advice

EYE CONTACT

- Flush immediately with water and seek medical advice
- Use of gloves recommended

SKIN CONTACT

- Wash skin with soap and water if irritation persists seek medical advice

IF INHALED

- Move to fresh air and seek medical advice if discomfort or other symptoms persist
- Ensure adequate ventilation during application