Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

FAST SET HI-STRENGTH CONCRETE

A high strength dry, concrete mix – made up of a combination of aggregate, sand and cement mixed together. Ideal for little fix up jobs around the home and building site.

Key Features

- ✓ Superior Strength 40MPa – Up to 60% stronger than regular concrete
- ✓ Ready to use - just add water
- ✓ Fast Initial Set Time – 15 minutes
- ✓ Water Resistant PE Bag
- ✓ 28 days until fully cured

Popular Uses

- Posts
- Fencing
- Pergolas
- Retaining walls
- Decks
- Other structural applications

Directions for use

- Remember to mix with water then place and lay in less than 5 minutes as it goes hard quickly
- Make sure your project is properly laid out with all the necessary tools at hand
- Pour required amount of concrete into a wheel barrow or onto a clean surface. Use contents as soon as possible after opening the package
- Add water gradually and mix thoroughly to a stiff consistency (one bag requires 300-345ml of clean water). Excess water can ruin good concrete. Do not add water after the concrete has been mixed as this reduces the strength of the concrete

Yield

- 1 x 10kg bag will cover 0.335m2 with thickness 15mm

Safety

RISK

- Cements may cause respiratory, skin and eye irritation
- Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitation (dermatitis)
- Repeated inhalation of dust containing silica may cause bronchitis, silicosis (scarring of the lung), lung cancer, and increases the risk of sclerodemna

THINGS TO WATCH

- Avoid contact with eyes and skin from wet and dry cement
- Do not breathe in dust
- Wear suitable protective clothing, including glove or barrier cream and eye protection
- Wear a P1 or P2 dust mask suitable for particulates when exposed to dust
- When cutting or abrading concrete, keep it wetted with water to avoid creation of hazardous dust
- Wash thoroughly after handling. Wash work clothes regularly

FIRST AID

- Irrigate eyes with plenty of water for 15 minutes and seek medical attention
- If inhaled, remove from dusty area. Seek medical attention if symptoms persist
- Wash skin with water

SPILLS/LEAKS

- Keep out of sewers and storm water

DISPOSAL

- Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines

MANUAL HANDLING

- This bag contains 20kg of product. It is recommended that all manual handling of this bag be undertaken by load shifting equipment
- Manual handling of this product without due care and attention could result in personal injury. Any manual handling should be understaken as a team lift. Prior to manual handling it is recommended that a manual handling risk assessment be undertaken