Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

FAST SET MORTAR

Dingo Fast Set Mortar is suitable for fast masonry repairs around the home and building site.

Key Features

- ✓ Sets in just 15 minutes
- ✓ Ready to use - just add water
- ✓ Ideal for little fix up jobs around the home and building site

Popular Uses

- Brickwork
- Grouting
- Patching

Directions for use

- Make sure your project is properly laid out with all the necessary tools at hand
- Pour required amount of Mortar into a wheel barrow or onto a clean surface. Use contents as soon as possible after opening the package
- Add water gradually and mix thoroughly to a stiff consistency (one bag requires approximately 1.9 litres of clean water).
- Should too much water be added, leave the micture aside until it thickens to workable consistency.
- You are now ready to trowel your mortar onto your bricks and blocks

Handy Hints

- Clay bricks should be lightly soaked in water before laying
- Concrete blocks should be laid dry
- Curing - Mortar should be kept damp or one week to help hardening. Retaining walls should not be backfilled for at least two weeks
- Storage - Keep dry prior to use. Unused contents must be kept dry

Yield

1 x 10kg bag will typically lay approximately 12 standard bricks with a 10mm joint (110mm thick).
1 x 10kg bag will typically lay approximately 7 standard blocks (100mm thick).

Safety

RISK

- Mixing cement may be irritating to the eyes and skin.
- Prolonged exposure to cement may cause dermatitis and alkaline burns.
- Cement dust is irritating to the eyes and skin and respiratory system.
- Repeated inhalation may increate bronchitis and silicosis.
- Crystaline silicais a known carcinogen.

SAFETY

- Avoid contact with eyes and skin with wet and dry cement.
- Wear suitable protective clothing including gloves and eye protection.
- Wear a suitable dust mask when handling cement or concrete, do not breathe in dust.
- Cutting concrete, keep it wet with water to avoid hazardous dust.

FIRST AID

- In the event of skin irritation wash with clean water.
- If dust gets into eyes wash immediately with eye wash solution or clean water.
- If symptoms persist seek medical advice.

MANUAL HANDLING

- This bag contains 10kg net of dry product.
- Manual handling of this bag without due care and attention could result in personal injury.

SAFETY DATA SHEETS

- For more information refer to the Safety Data Sheets at www.dingocement.com.au or call (+61) 3 8080 1420

DANGER

- Causes mild skin irritation.
- May cause respiratory irritation.
- May cause serious eye damage.
- May cause damage to lungs and respiratory problems through prolonged or repeated inhalation.