Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

HYDRATED LIME

Mix with sand and cement for improved mortar strength and workability.

Key Features

- ✓ Conforms to AS 1672.1
- ✓ Trade quality for top performance

Popular Uses

- Mixing with sand and cement to make mortar (enchances bond strength)
- Soil stabilisation
- Water treatment, gardening, white washing

Directions for use

For Mortar

- Combine your lime, sand and cement in the right proportions in a wheelbarrow or on a non porous surface
- Add some clean water and mix thoroughly
- Apply the mix with a trowel.

Handy Hints

A good mix for bricklaying is 6 parts sand, 1 part cement and 1 part Hydrated Lime.

Safety

RISK

- Cements may cause respiratory, skin and eye irritation
- Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitation (dermatitis)
- Repeated inhalation of dust containing silica may cause bronchitis, silicosis (scarring of the lung), lung cancer, and increases the risk of sclerodemna

THINGS TO WATCH

- Avoid contact with eyes and skin from wet and dry cement
- Do not breathe in dust
- Wear suitable protective clothing, including glove or barrier cream and eye protection
- Wear a P1 or P2 dust mask suitable for particulates when exposed to dust
- When cutting or abrading concrete, keep it wetted with water to avoid creation of hazardous dust
- Wash thoroughly after handling. Wash work clothes regularly

FIRST AID

- Irrigate eyes with plenty of water for 15 minutes and seek medical attention
- If inhaled, remove from dusty area. Seek medical attention if symptoms persist
- Wash skin with water

SPILLS/LEAKS

- Keep out of sewers and storm water

DISPOSAL

- Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines

MANUAL HANDLING

- This bag contains 20kg of product. It is recommended that all manual handling of this bag be undertaken by load shifting equipment
- Manual handling of this product without due care and attention could result in personal injury. Any manual handling should be understaken as a team lift. Prior to manual handling it is recommended that a manual handling risk assessment be undertaken