Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

STRUCTURAL GROUT

Dingo Structural Grout is a high strength, Class A structural grout that is shrinkage compensated, self levelling, and has been formulated to achieve high early strengths with low water addition levels.

Key Features

- ✓ 60MPa after 7 days
- ✓ Impact and vibration resistant
- ✓ High strength, adjustable consistency
- ✓ Initial set 3½ hours, Final set 4½ hours

Popular Uses

- Machine foundations
- Rail beds
- Columns in pre-cast construction
- Anchor bolts
- Bridge bearings
- Cavities
- Gaps
- Recesses
- High strength repair

Directions for use

- Make sure your project is properly laid out with all the necessary tools at hand.
- Pour required amount of Dingo Structural Grout into a clean bucket. Use contents as soon as possible after opening package.
- Measure water and add gradually until thoroughly mixed. 1 bag requires approximately 1.25 - 1.5L of clean water per 10kg.
- Initial set 3 ½ hours, Final set 4 ½ hours

Handy Hints

- Mix mechanically for at least 3 minutes with a low speed electric drill with paddle mixer.
- Surfaces should be clean, sound and free from oil, grease and loose particles

Yield

- 10kg of powder yields approximately 5.25L of grout

Safety

RISK

- Mixing Structural Grout may be irritating to the eyes and skin.
- Prolonged exposure to Structural Grout may cause dermatitis and alkaline burns.
- Structural Grout dust is irritating to the eyes and skin and respiratory system.
- Repeated inhalation may increase bronchitis and silicosis.
- Crystaline silica is a known carcinogen.

SAFETY

- Avoid contact with eyes and skin with wet and dry Structural Grout.
- Wear suitable protective clothing including gloves and eye protection.
- Wear a suitable dust mask when handling cement or concrete, do not breathe in dust.
- Cutting concrete, keep it wet with water to avoid hazardous dust.

FIRST AID

- In the event of skin irritation wash with clean water.
- If dust gets into eyes wash immediately with eye wash solution or clean water.
- If symptoms persist seek medical advice.

MANUAL HANDLING

- This bag contains 10kg net of dry product.
- Manual handling of this bag without due care and attention could result in personal injury.

DANGER

- Causes mild skin irritation.
- May cause respiratory irritation.
- May cause serious eye damage.
- May cause damage to lungs and respiratory problems through prolonged or repeated inhalation.