Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

STRUCTURAL MORTAR REPAIR

Dingo Structural Mortar Repair is a 1-component, polymer modified, fibre reinforced, low shrinkage, light weight repair mortar.

Key Features

- ✓ Meeting the requirements of class R3 of EN 1504-3
- ✓ Repair of spalled concrete caused by reinforcement corrosion
- ✓ Repairs with improved resistance to oils, sewage, chemicals etc
- ✓ Can be applied up to 75mm thick

Popular Uses

- Patching
- Cavities
- Brickwork Repair

Directions for use

- Make sure your project is properly laid out with all the necessary tools at hand
- Pour required amount of Dingo Structural Mortar Repair into a clean bucket. Use contents as soon as possible after opening package
- Measure water and add gradually until thoroughly mixed. 1 bag requires approximately 1.6 - 1.7L of clean water per 10kg. 10kg of powder yields approximately 6.5L of mortar

Handy Hints

- Mix mechanically for at least 3 minutes with a low speed electric drill with paddle mixer
- Surfaces should be clean, sound and free from oil, grease and loose particles

Yield

- 10kg of powder yields approximately 6.5L of mortar

Safety

RISK

- Mixing Structural Mortar Repair may be irritating to the eyes and skin. Prolonged exposure to Structural Mortar Repair may cause dermatitis and alkaline burns. Structural Mortar Repair dust is irritating to the eyes and skin and respiratory system. Repeated inhalation may increate bronchitis and silicosis. Crystaline silicais a known carcinogen.

SAFETY

- Avoid contact with eyes and skin with wet and dry Structural Mortar Repair.
- Wear suitable protective clothing including gloves and eye protection.
- Wear a suitable dust mask when handling cement or concrete, do not breathe in dust.
- Cutting concrete, keep it wet with water to avoid hazardous dust.

FIRST AID

- In the event of skin irritation wash with clean water.
- If dust gets into eyes wash immediately with eye wash solution or clean water.
- If symptoms persist seek medical advice.

MANUAL HANDLING

- This bag contains 10kg net of dry product.
- Manual handling of this bag without due care and attention could result in personal injury.

SAFETY DATA SHEETS

- For more information refer to the Safety Data Sheets at www.dingocement.com.au or call (+61) 3 8080 1420

DANGER

- Causes mild skin irritation.
- May cause respiratory irritation.
- May cause serious eye damage.
- May cause damage to lungs and respiratory problems through prolonged or repeated inhalation.