Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

FLASHCRETE

Dingo Flashcrete Mortar is a mixture of cement, quality sand and specialty additives.

Key Features

- ✓ Hardens in 5 minutes
- ✓ Ready to use - just add water

Popular Uses

- Repairs to sand/cement renders
- Shower bases
- Patching around electric and plumbing fittings
- Covering pipework

Directions for use

BE AWARE OF SHORT MIXING TIME AND PLACE IN UNDER 3 MINUTES

- Do not use mechanical mixer.
- If priming surfaces with water, use of an acrylic bonding agent assists with adhesion.

MIX IN BUCKET

- Add 1.1L of water into bucket.
- Place lid back on firmly, roll and shake bucket for 1 minute and place immediately.

OR

MIX IN WHEELBARROW

- Empty contents into wheelbarrow.
- Add 1.1L of water.
- Mix thoroughly for 1 minute and place immediately.
- Moist cure when practical. Wet down joint periodically for 7 days.

Yield

1 x 8kg pail = 0.5m² at 10mm thick

Safety

THIS PRODUCT CONTAINS CEMENT

RISK

- Cement powder and sand dust is irritating to the eyes, respiratory system and skin.
- It may cause sensitisation through skin contact (dermatitis).

Safe Handling

- Avoid contact with the skin and eyes.
- Wear suitable protective clothing, boots, gloves and eye protection.
- Avoid breathing dust by wearing suitable respiratory equipment.
- Manual handling of this bag without due care and attention could result in personal injury. Unless you are trained in manual handling of heavy loads, it is recommended that you share the load with another person.

FIRST AID

- Eyes: Rinse immediately with plenty of clean water.
- Inhaled: Move immediately to fresh air.
- Swallowed: Wash mouth with water. Do not induce vomiting. Drink water or milk to dilute stomach contents. Seek medical attention.
- Skin: Wash immediately with clean water. (Seek medical attention if irritation persists).

DISPOSAL

- This material and its package must be disposed of in a safe way.
- Do not empty into drains. Spills may be vacuumed or swept. Avoid generation of dust.

Additional information is listed in the Material Safety Data Sheet.