Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

FAST SET CONCRETE

A specialised blend of fast-setting cement, sand and stone that is perfect for jobs where fast completion is required.

Key Features

- ✓ Hardens in 15 minutes
- ✓ Set non-structural posts without mixing
- ✓ Ready to use - just add water
- ✓ 30MPa after 28 days

Popular Uses

- Posts and uprights
- Letterboxes and clotheslines
- General concreting
- Time limited jobs

Directions for use

- Thoroughly wet the hole first so none of the water in the Dingo Fast Set Concrete will be absorbed by dry soil conditions. Pour the required amount of water into the hole and then add Dingo Fast Set Concrete. NO NEED TO MIX and add straight from the bag. For best results, add 2.5 litres of clean water per 20 kg bag to the already pre-wet soaked hole (excess water will reduce strength and cause longer setting time). Not suitable where smooth trowel finish is required.
- Immediately add your Fast Set Concrete around the post and compact it well using a sturdy piece of 40 x 20 timber. Ensure the water reaches the top of the concrete mix in the hole. Never mix Dingo Fast Set Concrete in a barrow or cement mixer.
- Fast Set Concrete will have an initial set in approximately 15 minutes. Leave post supports in place for at least 45 minutes. Do not apply any load to the post for at least 2 hours.

Yield

- 1 x 20kg bag will cover 0.67m2 with thickness 15mm

Safety

RISK

- Cements may cause respiratory, skin and eye irritation
- Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitation (dermatitis)
- Repeated inhalation of dust containing silica may cause bronchitis, silicosis (scarring of the lung), lung cancer, and increases the risk of sclerodemna

THINGS TO WATCH

- Avoid contact with eyes and skin from wet and dry cement
- Do not breathe in dust
- Wear suitable protective clothing, including glove or barrier cream and eye protection
- Wear a P1 or P2 dust mask suitable for particulates when exposed to dust
- When cutting or abrading concrete, keep it wetted with water to avoid creation of hazardous dust
- Wash thoroughly after handling. Wash work clothes regularly

FIRST AID

- Irrigate eyes with plenty of water for 15 minutes and seek medical attention
- If inhaled, remove from dusty area. Seek medical attention if symptoms persist
- Wash skin with water

SPILLS/LEAKS

- Keep out of sewers and storm water

DISPOSAL

- Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines

MANUAL HANDLING

- This bag contains 20kg of product. It is recommended that all manual handling of this bag be undertaken by load shifting equipment
- Manual handling of this product without due care and attention could result in personal injury. Any manual handling should be understaken as a team lift. Prior to manual handling it is recommended that a manual handling risk assessment be undertaken