Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

CONCRETE MIX

Suitable for a wide variety of general concreting, pathways, small concrete slabs, garden edging, posts and footings. A drymix combination of aggregate, sand and cement, ready for the addition of water.

Key Features

- ✓ Simple to use pre-mixed concrete - just add water
- ✓ 25MPa after 28 days
- ✓ Conforms to AS 3648

Popular Uses

- General concreting
- Pathways
- Landscaping
- Plumbing

Directions for use

- Empty bag into a wheelbarrow or on to a non porous surface. If you want to colour your concrete you should ass colour oxide in the prescribed manner
- Add clean water (one bag requires 2.1-2.6 litres) slowly and mix until a stiff, but workable consistency is achieved. Too much water will make the concrete weak
- For best results, compact the concrete well after placements, screed level with a board, trowel smooth if required and then keep mist for seven days

Yield

No. of bags of 20kg required for a 75mm thick slab of the following dimensions:

Length x width	500	750	1000	1500	1750	2000
500	2	3	4	6	7	8
750	3	4.5	6	9	10.5	12
1000	4	6	8	12	14	16

Safety

RISK

- Cements may cause respiratory, skin and eye irritation
- Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitation (dermatitis)
- Repeated inhalation of dust containing silica may cause bronchitis, silicosis (scarring of the lung), lung cancer, and increases the risk of sclerodemna

THINGS TO WATCH

- Avoid contact with eyes and skin from wet and dry cement
- Do not breathe in dust
- Wear suitable protective clothing, including glove or barrier cream and eye protection
- Wear a P1 or P2 dust mask suitable for particulates when exposed to dust
- When cutting or abrading concrete, keep it wetted with water to avoid creation of hazardous dust
- Wash thoroughly after handling. Wash work clothes regularly

FIRST AID

- Irrigate eyes with plenty of water for 15 minutes and seek medical attention
- If inhaled, remove from dusty area. Seek medical attention if symptoms persist
- Wash skin with water

SPILLS/LEAKS

- Keep out of sewers and storm water

DISPOSAL

- Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines

MANUAL HANDLING

- This bag contains 20kg of product. It is recommended that all manual handling of this bag be undertaken by load shifting equipment
- Manual handling of this product without due care and attention could result in personal injury. Any manual handling should be understaken as a team lift. Prior to manual handling it is recommended that a manual handling risk assessment be undertaken