Section 1 - Identification

Dingo Cement Pty Ltd **Phone: 03 8080 1420 (any time)**
Unit 8, 25-37 Huntingdale Road
Burwood VIC 3125 AUSTRALIA

Chemical nature: Concrete mix.

Trade Name: **Dingo All Rounder Concrete Mix**

Product Use: Used as a construction material and for similar purposes.

Creation Date: **June, 2025**

This version issued: **June, 2025** and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

UN Number: None allocated

GHS Signal word: DANGER

Skin Irritation Category 2
Skin Sensitisation Category 1
Eye damage Category 1
Specific Target Organ Toxicity - Single Exposure Category 3

HAZARD STATEMENT:

H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.

PREVENTION

P261: Avoid breathing dusts.
P262: Do not get in eyes, on skin, or on clothing.
P264: Wash contacted areas thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P310: Immediately call a POISON CENTRE or doctor/physician.
P335: Brush off loose particles from skin.
P362: Take off contaminated clothing and wash before reuse.
P363: Wash contaminated clothing before reuse.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313: If skin irritation or rash occurs: Get medical advice.
P370+P378: In case of fire: Use carbon dioxide, dry chemical, foam, water fog, to extinguish.

STORAGE

P410: Protect from sunlight.
P402+P404: Store in a dry place. Store in a closed container.
P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Concrete blend.
Odour: No odour.

Section 3 – Composition and Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m^3)	STEL (mg/m^3)
Quartz	14808-60-7	60-80	0.05	not set
Portland cement	65997-15-1	10-20	10	not set
Cement, alumina, chemicals	65997-16-2	<5	not set	not set
Calcium sulfate	7778-18-9	<5	10	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.
Skin Contact: Quickly and gently brush away excess particles. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 20 minutes by the clock. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard.
Eye Contact: Quickly and gently brush particles from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.
Ingestion: If swallowed, do NOT induce vomiting. Immediately contact a Poisons Information Centre, or call a doctor. Wash mouth with water. If vomiting occurs naturally, lay patient on side, in recovery position as there is a chance that vomitus may enter airways causing harm to lungs.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.
Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.
Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam or water fog.
Fire Fighting: When fighting fires involving significant quantities of this product, no special equipment is believed to be necessary.

Section 6 - Accidental Release Measures

Accidental release: Minor spills do not normally need any special cleanup measures. In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC and Nitrile. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that dusts are likely to build up in cleanup area, we recommend that you use a suitable dust mask. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	**TWA (mg/m^3)**	**STEL (mg/m^3)**
Silica	0.05	not set
Portland cement	10	not set
Calcium sulfate	10	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC, nitrile.

Respirator: If there is a significant chance that dusts are likely to build up in the area where this product is being used, we recommend that you use a suitable dust mask. Otherwise, not normally necessary.

Eyebaths or eyewash stations should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Concrete blend.
Odour:	No odour.
Freezing/Melting Point:	No specific data. Solid at normal temperatures.
Boiling Point:	Not available.
Flash point:	No data
Upper Flammability Limit:	No data.
Lower Flammability Limit:	No data.
Autoignition temperature:	No data.
Flammability Class:	No data.
Volatiles:	No data.
Vapour Pressure:	No data.
Vapour Density:	Not applicable.
Specific Gravity:	No data.
Water Solubility:	Insoluble.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.

Evaporation Rate:	Not applicable.
Coeff Oil/water Distribution:	No data
Particle Characteristics:	A blend of particles of widely varying sizes. The respirable content is unlikely to contain significant quantities of silica.
Viscosity:	Not applicable.

Section 10 - Stability and Reactivity

Reactivity: If exposed to water prior to use, the cement will set and the product will not be suitable for its intended use. Mixture with acids is expected to liberate carbon dioxide gas. In large quantities and/or in confined areas, this may displace oxygen in the air, leading to an asphyxiation hazard.
Conditions to Avoid: None known.
Incompatibilities: water, acids.
Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form oxides of sulfur (sulfur dioxide is a respiratory hazard) and other sulfur compounds. Most will have a foul odour. Calcium compounds, aluminium compounds, silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.
Polymerisation: Polymerisation reactions are unlikely. They are not expected to occur.

Section 11 - Toxicological Information

Local Effects:
Target Organs: This product may affect lungs, eyes, skin. Ingredients in this product have an established TWA, so exposure by inhalation should be avoided.

Major Health Hazards: may cause an allergic skin reaction, causes serious eye damage, causes skin irritation, may cause respiratory irritation.

Classification of Hazardous Ingredients

Ingredient	Health Hazard Statement Codes
Silica (respirable content)	H350i, H372

- Carcinogenicity – category 1A
- Specific target organ toxicity (repeated exposure) – category 1

Potential Health Effects

Inhalation:
Short Term Exposure: product may be irritating, although unlikely to cause anything more than transient discomfort.
Long Term Exposure: Long term inhalation of high amounts of any nuisance dust may overload lung clearance mechanism. No data for health effects associated with long term inhalation.

Skin Contact:
Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.
Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:
Short Term Exposure: This product is corrosive to eyes. It will cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring is likely.
Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:
Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is not harmful. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.
Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: Silica is classified by SWA as a Category 1a Carcinogen
See the SWA website for further details. A web address has not been provided as addresses frequently change.
NTP: No significant ingredient is classified as carcinogenic by NTP.
IARC: Silica is classed 1 by IARC - carcinogenic to humans.
See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

This product is unlikely to adversely effect the environment. Salts, acids and bases are typically diluted and neutralised when released to the environment in small quantities.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with AICIS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)
AICS/AIIC	Australian Inventory of Industrial Chemicals
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document “Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice” (July 2020) and GHS Revision 7

Copyright © Kilford & Kilford Pty Ltd, June, 2025.

http://www.kilford.com.au/ Phone (02)8321 8866