Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version August 2026

ALL ROUNDER

Dingo All-Rounder™ is a high-performance, easy-to-use concrete mix designed for every job. From slabs and pathways to posts (works with aluminium posts) and footings, it is the perfect all rounder. It delivers 40MPa structural strength, provides around 30 minutes of working time, and sets in just 45 minutes, making it reliable and efficient.

Item Number – 1021917

Key Features

- ✓ 30 minute working time, sets in 30-45 minutes
- ✓ Structural Strength at 40MPa
- ✓ Versatile concrete mix for a wide variety of jobs, big and small
- ✓ Great for slabs, shade sails, leisure equipment
- ✓ Lower Carbon Formula

Popular Uses

- Slabs
- Footings
- Pergolas
- Shade Sales
- Leisure Equipment

Directions for use

USAGE INSTRUCTIONS

- Use 2-2.4L of clean, drinkable water per 20kg bag. Do not exceed 2.6L of water per bag. Do not add any additional additives

Mechanical Mixing

- The use of a mortar mixer, concrete mixer, or a drill-mounted mixer is recommended.
- Place the desired quantity of mix water into the mixing container.
- While the mixer is running, add concrete mix.
- Mix for the minimum amount of time required to achieve a lump-free, uniform consistency (usually 1-3 minutes).
- Let mixture stand 1-2 minutes before mixing again until desired consistency is achieved

Hand Mixing

- Place the desired quantity of mix water into the mixing container.
- Add concrete mix and blend using a shovel or hoe.
- Turn and fold the mix until a lump-free, uniform consistency is achieved.
- Let mixture stand 1-2 minutes before mixing again until desired consistency is achieved

Yield

1 bag (20kg) will yield approximately 1m2 at 10mm thickness.

Square Metres (m2)	Slab Thickness	
	75mm	100mm
1	8 bags	10 bags
2	15 bags	20 bags
3	23 bags	30 bags
4	30 bags	40 bags
5	38 bags	50 bags
6	45 bags	60 bags
7	53 bags	70 bags
8	60 bags	80 bags
9	68 bags	90 bags
10	75 bags	100 bags

Safety

THIS PRODUCT CONTAINS CEMENT RISK

Cement powder and sand dust is irritating to the eyes, respiratory system and skin. It may cause sensitisation through skin contact (dermatitis).

SAFETY

Safe Handling

- Avoid contact with the skin and eyes.
- Wear suitable protective clothing, boots, gloves and eye protection.
- Avoid breathing dust by wearing suitable respiratory equipment.
- Manual handling of this bag without due care and attention could result in personal injury. Unless you are trained in manual handling of heavy loads, it is recommended that you share the load with another person.

FIRST AID

- Eyes: Rinse immediately with plenty of clean water.
- Inhaled: Move immediately to fresh air.
- Swallowed: Wash mouth with water. Do not induce vomiting. Drink water or milk to dilute stomach contents. Seek medical attention.
- Skin: Wash immediately with clean water.(Seek medical attention if irritation persists).

SAFETY

Disposal

- This material and its package must be disposed of in a safe way.
- Do not empty into drains. Spills may be vacuumed or swept. Avoid generation of dust. Additional information is listed in the Material Safety Data Sheet