Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version July 2025

MAXPRO CONCRETE MIX

MaxPRO Concrete Mix is a fibre reinforced, rapid hardening concrete formulated to provide a 1 hour working time and a walk on time of 4 hours. Achieves a compressive strength of 50MPa after 28 days. The mix provides superior workability and finishing characteristics and resists drying shrinkage cracks.

Key Features

- ✓ Workable for 1 Hour
- ✓ Walk on in 4 Hours
- ✓ Fibre reinforced to resist shrinkage cracks
- ✓ Conforms to AS 3648
- ✓ Ready to use - just add water
- ✓ Excellent workability
- ✓ 50MPa after 28 days

Popular Uses

- Slabs
- Pathways
- Footings
- Posts
- Garden edges
- Driveways
- Benchtops

Directions for use

- Make sure your project if properly laid out with all the necessary tools at hand
- Pour required amount of concrete into a wheel barrow or onto a clean surface. Use contents as soon as possible after opening the package
- Calculate the amount of water you will need. One bag requires 2-2.3 litres of clean water (Milk cartons make handy measures)
- Add water gradually and mix thoroughly to a stiff consistency. Excess water can ruin good concrete. Do not add water after the concrete has been mixed as this reduces the strength of concrete

Yield

1 x 20kg bag will cover 0.67m2 with thickness 15mm

Bag's Required

SQM's	No of Bags
10	108
9	98
8	99
7	76
6	66
5	54
4	44
3	34
2	22
1	12
Depth:	100mm

Safety

RISK

- Cements may cause respiratory, skin and eye irritation
- Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitation (dermatitis)
- Repeated inhalation of dust containing silica may cause bronchitis, silicosis (scarring of the lung), lung cancer, and increases the risk of sclerodemna

THINGS TO WATCH

- Avoid contact with eyes and skin from wet and dry cement
- Do not breathe in dust
- Wear suitable protective clothing, including glove or barrier cream and eye protection
- Wear a P1 or P2 dust mask suitable for particulates when exposed to dust
- When cutting or abrading concrete, keep it wetted with water to avoid creation of hazardous dust
- Wash thoroughly after handling. Wash work clothes regularly

FIRST AID

- Irrigate eyes with plenty of water for 15 minutes and seek medical attention
- If inhaled, remove from dusty area. Seek medical attention if symptoms persist
- Wash skin with water

SPILLS/LEAKS

- Keep out of sewers and storm water

DISPOSAL

- Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines

MANUAL HANDLING

- This bag contains 20kg of product. It is recommended that all manual handling of this bag be undertaken by load shifting equipment
- Manual handling of this product without due care and attention could result in personal injury. Any manual handling should be understaken as a team lift. Prior to manual handling it is recommended that a manual handling risk assessment be undertaken