Dingo Cement Pty Ltd
Unit 8, 25-37 Huntingdale Rd
Burwood VIC 3125. Australia

Phone: +61 (3) 8080 1420
info@dingocement.com.au
www.dingocement.com.au

PRODUCT DATA SHEET

Version September 2026

BITUMEN PATCH

Watch video here

An easy-to-use Cold Mix Bitumen formula designed for small repairs to potholes, driveways, paths and other applications where Bitumen is required. Specifically engineered to remain somewhat pliable following application. This assists in eliminating small voids and crevices through the compaction process

Item Number – 1078383

Key Features

- ✓ Ready to use (no mixing required)
- ✓ Just pour and compact
- ✓ Fast, easy and permanent
- ✓ Open to traffic immediately

Popular Uses

- ✓ Potholes
- ✓ Driveways
- ✓ Footpaths
- ✓ General repairs

Directions for use

Please read carefully before opening packaging and view application instruction video from QR code.

Surface Preparation
Area where product is to be used must be dry. Remove any weeds or other plant material (use of weed killer recommended) to create a clean surface for the bitumen to be compacted into. For footpaths use timber or other material to assist forming edges. Base must be thoroughly compacted, crushed stone recommended.

Application
Use contents immediately upon opening. Contents will be firm upon removal from bucket. Tip bucket upside down to remove contents and separate with a shovel or similar tool. Once the Bitumen is fully separated apply Bitumen evenly, spreading the mixture into the edges of the area and creating a slight dome shape over the area in preparation for compaction. Do not exceed 30mm in one application. Leave for a few minutes and then compact using a roller, plate compactor or hand tamper. A 30mm layer should compact to around 25mm. For thicknesses greater than 50mm Dingo Bitumen Patch is not recommended. Note, in cooler weather the Bitumen will feel firm when removed from packaging but will still perform in temperatures between 10 and 40 degrees Celsius. If you wish to soften up the Bitumen, place in a warm place for up to 30 minutes.

Safety

IF SWALLOWED
- Drink water, seek medical advice

EYE CONTACT
- Flush immediately with water and seek medical advice.
- Use of gloves recommended

SKIN CONTACT
- Wash skin with soap and water if irritation persists seek medical advice

IF INHALED
- Move to fresh air and seek medical advice if discomfort or other symptoms persist
- Ensure adequate ventilation during application

Yield

60kg of Dingo Bitumen will cover approximately 1m² at a depth of 23mm.